



NIPPON KAIJI KYOKAI

TYPE APPROVAL CERTIFICATE

Certificate No. TA25074M


This is to certify that the undernoted products have been approved in accordance with the requirements 12.3.3, Part D of the “Rules for the Survey and Construction of Steel Ships” and Chapter 9, Part 6 of the “Guidance for the Approval and Type Approval of Materials and Equipment for Marine Use”.

This certificate is issued to

Manufacturer:	SWAGELOK COMPANY
Place of manufacture	29500 Solon Road, Solon, Ohio 44139 U.S.A
Product description:	DOUBLE FERRULE TYPE TUBE FITTINGS
Type designation(s):	SWAGELOK TUBE FITTINGS
Test standards:	IACS UR P2
Approval No.:	95FV101B
Valid until:	31 January 2030

The details are described in the attached sheets.

Issued at Tokyo on 27 January 2025.


S. Oishi
General Manager
Machinery Department



• **Particulars and Conditions**

Series	Tube Size	Design Pressure (MPa)	Design Temperature (°C)	Material
100 ~ 3200	1/16 ~ 2B	22.57 ~ 77.50	-196 ~ 93	SUS316 (316 Stainless Steel)
		20.61 ~ 73.58	-196 ~ 204	
		17.66 ~ 65.73	-196 ~ 300	
200 ~ 1610	1/8 ~ 1B	29.43 ~ 69.66	-40 ~ 40	NCuP (Alloy 400)
		25.51 ~ 60.83	-40 ~ 93	
		22.57 ~ 54.94	-40 ~ 300	
3 ~ 38MO	3 ~ 38A	29.43 ~ 62.79	-196 ~ 93	SUS316 (316 Stainless Steel)
		26.49 ~ 59.85	-196 ~ 204	
		23.55 ~ 52.98	-196 ~ 300	
6 ~ 25MO	6 ~ 25A	20.61 ~ 56.90	-40 ~ 40	NCuP (Alloy 400)
		17.66 ~ 50.04	-40 ~ 93	
		15.70 ~ 44.15	-40 ~ 300	

Note: Design pressure, design temperature and materials are specified in accordance with the manufacturer's catalogs. (No. MS-01-140 "Gaugeable Tube Fittings and Adapter Fittings" and No. MS-01-107 "TUBING DATA")

Part Material	Kind of Fluid
SUS316 (316 Stainless Steel)	Air, Hydraulic oil, Lubricating oil, Fuel oil, Steam, Fresh water, Natural gas*
NCuP (Alloy 400)	Air, Hydraulic oil, Lubricating oil, Fuel oil, Fresh water, Sea water

*Minimum operating temperature to be 0 °C or above when the fluid is natural gas.

• **Type Approval Test**

Tightness test, Vibration test, Pressure pulsation test, Burst pressure test, Pull-out test,
Repeated assembly test

• **Limitations**

1. The installation of mechanical joints to be in accordance with the manufacturer's assembly instructions and 12.3.3, Part D of the Rules for the Survey and Construction of Steel Ships (hereinafter referred to as "the Rules").
2. The pipe fittings not to be used for suction lines.

• **Production Test**

1. The pipe fittings used for piping belonging to Group I & II defined by 12.1.3, Part D of the Rules to be subjected to hydraulic test in the presence of the Society's surveyor in accordance with 12.6.1, Part D of the Rules.
2. The pipe fittings used for piping of natural gas services to be subjected to hydraulic test in the presence of the Society's surveyor in accordance with 5.13.2, Part N of the Rules.

• **Notice**

Any significant changes in design or construction of the above items may render this certificate invalid.

- The End -