| Joel Feldman, Vice President, Engineering (see note 3) employed by Swagelok Company and being the person having full authority and responsibility for the quality of the end product do solemnly declare that the information contained in this form is true and to the best of my knowledge represents the product for which registration is sought. The dimensions, materials of construction, pressure temperature ratings, and identification markings are in accordance with the herein named standards. I further declare that the manufacture of these fittings is regulated by a Quality Control Program which extends to each plant where fabrication occurs in whole as being suitable for that purpose and I make this solemn or in part and has been verified by BSI declaration conscientiously believing it to be true, and knowing that it is of the same force and effect as if made under oath. 4/2/2021 | 8:11 AM EDT Signature of Declarer: Declared before me at nable to get a notary USETHIS SPACE FOR THE day of signature or Seal due to OFFICIAL SEAL Commissioner of Oaths or Notary Public: (sign) COVID-19 situation

(Affix Official seal to the right)

This space for Regulatory Authority use
This registration must be revalidated after ten (10) years from the date of acceptance.

CRN: OA 23291.5

FID#: 1214

Notes:

DECLARATION:

1. All fittings shall be registered in the name of the Manufacturer.

Each category shall be supported with two Statutory Declaration forms and one copy of supporting documentation.

The declaration shall be made by the person having full authority and responsibility for the quality of the end product.

Quality control programs shall be resubmitted for validation at a maximum interval of five (5) years.





THIS IS PART OF CRN
0A23291.5
Technical Standards and Safety Authority
Boilers and Pressure Vessels Safety
Program

Date: March 8, 2021 Page 1 of 3

# Attachment B. Scope of Registration for Swagelok Alloy 825 (ASTM B425 UNS N08825) Tube Fittings (Category A)

This document presents the scope of Swagelok Nickel-Chromium Alloy 825 Tube Fittings covered by this submission for CRN approval. These fittings have been evaluated in accordance with ASME B31.1-2020 and ASME B31.3-2018 for unlisted components.

The fittings rating is based on the lower rating between the type of end connections. **Summary Table** 

	Material (Standard)	Port Connections and Sizes	Maximum Allowable Working Pressure			
Product Description or Series			Up to 100°F (psig)	At maximum temperature per ASME B31.3 (psig)	At maximum temperature per ASME B31.1 (psig)	Design Code of Construction
Gaugeable Tube Fittings and Adapter Fittings	Alloy 825, UNS N08825 (ASTM B425) For straight fittings, hardware Alloy 825, UNS N08825 (ASTM B564) For shaped fittings	Tube Fitting 1/4 - 1/2 inch, 6 - 12mm	See Table below	See Table below	See Table below	Unlisted Component in ASME B31.1 & B31.1
		NPT, Male 1/16 - 1 inch	11 600 - 6100	11 449 – 6021* at 800°F (426°C)	8468 - 4453* at 800°F (426°C)	ASME B1.20.1 is listed in ASME B31.1 & B31.3
		NPT, Female 1/16 - 1 inch	7800 - 5100	7699 - 5034* at 800°F (426°C)	5694 - 3723* at 800°F (426°C)	

<sup>\*\*</sup>Rating for fitting material (may be limited by thread sealant)

#### Alloy 825 Swagelok Tube Fitting Pressure Rating Tables


	Maximum Allowable Working Pressure				
Swagelok End Connection Size	Up to 100°F	At maximum temp. 800°F (426°C) per ASME B31.3	At maximum temp. 800°F (426°C) per ASME B31.1		
1/4 inch	11600 psig	11 449 psig	8468 psig		
3/8 inch	8200 psig	8093 psig	5986 psig		
1/2 inch	5900 psig	5823 psig	4307 psig		
6 mm	660 bar	651 bar	482 bar		
10 mm	480 bar	474 bar	350 bar		
12 mm	480 bar	474 bar	350 bar		



Canadian Registration Number Submittal Category A: Swagelok Alloy 825 Tube Fittings

#### **Product Description**


Swagelok Fittings are furnished in a variety of configurations and shapes (straight, elbow, or tee). Swagelok Fittings consist of at least one Swagelok End – a two-ferrule mechanical-grip design. The Swagelok end is a proprietary design, and the assembly consists of Swagelok body, nut, front and back ferrule (see detail). The table above, as well as the "Configurations" section, covers a variety of other end connections.







### **Configurations**


Unions (Straight, Elbow, Tee)
 Swagelok Tube Fitting End Connections










2. Male and Female Connectors / Adapters (Straight, Elbow, Tee)
Swagelok Tube Fitting End Connection to an NPT End Connection









Date: March 8, 2021

Page 2 of 3

Swagelok to NPT Male Connectors

Swagelok to NPT Female Connectors

(For dimensions see catalog.)



Canadian Registration Number Submittal Category A: Swagelok Alloy 825 Tube Fittings

#### **Product Options:**

The product options listed below affect pressure and/or temperature ratings shown in the above Summary Table, but in all cases the ratings are less than, or equal to, those shown in the table.

Date: March 8, 2021

Page 3 of 3

- 1. Bored-Through Fittings.
- 2. Sealant for tapered pipe threads (NPT):
  - a. Curable resin with PTFE
  - b. PTFE tape

Additional options that do not affect pressure and/or temperature ratings may be made available within the scope of this approval. Examples of these would include the following:

- 1. Special marking
- 2. Special cleaning
- 3. Wire drills
- 4. Bulkhead Configurations
- 5. Snubbers/frits and orifice plates
- 6. Equivalent metric or fractional hex sizes

All the above options, those that affect pressure and/or temperature ratings and those that do not, are within the scope of this approval.

#### **Quality System**

The Swagelok Company quality system complies with the requirements of ISO 9001:2015. The Swagelok Company maintains BSI Certificate of Registration Number FM 01729, which applies to all locations listed on the Certificate.

#### References

The product catalog does not represent the full scope of the registration but rather details some of the most common options.

- Gaugeable Tube Fittings and Adapter Fittings MS-01-140, Rev AE
- Swagelok Tubing Data Sheet MS-01-107, Rev T

## THIS IS PART OF CRN

0A23291.5

Technical Standards and Safety Authority
Boilers and Pressure Vessels Safety
Program

# **Attachment A. Swagelok Manufacturing Locations**

This document lists the Swagelok locations where end item or component level manufacturing activities take place.

Swagelok Company	Swagelok Company (Falon 1)	
29500 Solon Road	348 Bishop Road	
Solon, Ohio 44139	Highland Heights, Ohio 44143	
USA	USA	
Swagelok Company (Highland)	Swagelok Company (Falon 2)	
318 Bishop Road	358 Bishop Road	
Highland Heights, Ohio 44143	Highland Heights, Ohio 44143	
USA	USA	
Swagelok Company (OFC)	Swagelok Company (HPF)	
29495 F.A. Lennon Drive	6050 Cochran Road	
Solon, Ohio 44139	Solon, Ohio 44139	
USA	USA	
Swagelok Company (Atlantic)	Swagelok Company (Snow Metal)	
26651 Curtiss Wright Parkway	6060 Cochran Road	
Willoughby Hills, Ohio 44092	Solon, Ohio 44139	
USA	USA	
Swagelok Company (Micro) 26653 Curtiss Wright Parkway Willoughby Hills, Ohio 44092 USA	Swagelok Company (Alfred) 29500 Ambina Drive Solon, Ohio 44139	
Swagelok Hose Services Company (SHSC)	Swagelok Company (Strongsville)	
29900 Solon Industrial Parkway	15400 Foltz Road	
Solon, Ohio 44139	Strongsville, Ohio 44119	
Swagelok (China) Fluid System Technologies Ltd. Changshu Export Process Zone Changshu Economic Development Zone Changshu, Jiangshu 215513 China	Swagelok Limited Ballafletcher Road Tromode IM4 4RA Isle of Man	